

SUBDIVISIONS T. 18 N., R. 54 E.

CHAINS

- 59.80 Bottom of canyon, wash, 20 lks. wide, 8 ft. deep, drains S.
General ascent of E. slope
- 62.90 Lincoln highway, bears N. and S.
- 73.60 Draw, drains SE.
- 79.90 Point for the cor. of secs. 29, 30, 31 and 32, hereinafter established

Land, rough mountainous. Soil, rocky.

Timber, pinon and juniper. Undergrowth, sagebrush.

Fair grazing. General drainage, S.

West, on sectional correction line bet. secs. 30 and 31

Asc. steep rocky E. slope 530 ft. to

- 18.95 Sharp rocky spur, projects S. Desc. steep rocky W. slope
155 ft. to saddle and head of draw, draining SE.

- 24.00 Saddle. Draw draining SE.
Asc. steep rocky SE. slope 370 ft. to

- 40.00 On steep rocky SE. slope

Set an iron post, 3 ft. long, 1 in. dia., 10 ins. in the
ground to solid rock, in a mound of stone, for $\frac{1}{4}$ sec.
cor., with brass cap mkd

$\frac{1}{4}$ S 30

S 31
1924

At base of post deposit a marked(x) stone, $\frac{1}{2} \times 2 \times 2$ ins.

Asc. steep rocky SE. slope 110 ft. to

- 44.05 Ridge, bears N. and S, Desc. general SW. slope across
ravines and low spurs 330 ft. to

- 71.60 Ravine, drains S. Asc. E. slope 40 ft. to

- 74.00 Spur, projects S. Desc. W. slope 190 ft. to

- 84.43 Intersect W. bdy. of township, and

Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the
ground, for closing cor. of secs. 30 and 31, with brass
cap mkd

T18N

R53E R54E

S30 c

S31 c

1924

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.