

INDEPENDENT

RESURVEY OF WEST BDY. OF T. 16 N., R. 26 E.

CHAINS From the SW. closing cor. of T. 16 N., R. 26 E.
 N 0° 14' E., on true W. bdy of sec. 31
 Asc. steep rocky SW. slope 275 ft. to
 2.60 Rocky spur, projects W; descend slight NW. slope 15 ft. to
 4.53 Old standard SE. cor. of T. 16 N., R. 25 E., which is a
 stone, firmly set in a mound of stone, and marked and
 witnessed as described by the Surveyor General, bears
 W. 2 lks. dist. I destroy all traces of this cor. and
 on this line

Set an iron post, 3 ft long, 3 ins. in dia., 8 ins. in
 rocky ground, surrounded by a mound of stone, At base
 of post deposit stone 4x4x2 ins. mkd with(x)cross, for
 the standard SE. cor. of T. 16 N., R. 25 E., with brass
 cap of post marked

```

      T16N
      SC
R25E | R26E
      S36
-----|
      S1 | S31
      T15N
  
```

1923

Ascend along numerous small rocky spurs and ravines with
 a general easterly drainage 60 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 12 ins. in
 ground to solid rock, surrounded by a mound of stone,
 for $\frac{1}{2}$ sec. cor. of sec. 31 only, with brass cap mkd.

```

      |
      |  $\frac{1}{2}$ 
      |
      | S31
  
```

1923

Deposit volcanic rock 6x4x4 ins., mkd with(x)cross at
 base of post.

Find no trace of old $\frac{1}{2}$ sec. cor.

Asc. across numerous spurs and ravines with general
 easterly drainage 215 ft. to

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 14 ins. in
 ground to solid rock, surrounded by mound of stone, for
 cor. of secs. 30 and 31, with brass cap marked