	9	, -1	DEPENDENT RESURVEY OF PORTION OF S. BDY. T. 32 N., R. 29 E.
			Land, rolling. Soil, sandy and rocky.
			Timber, none. Undergrowth, sage.
			SURVEY OF PORTION OF S. BDY. T. 32 N. R. 29 E.
			From the cor. of secs. 1 and 2
			West, on S. bdy. of sec. 35
	*		Over gently rolling land
	9	12.70	Road, N. to Sulphur and S. to Seven Troughs
		39.38	Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
		,	the ground, for $\frac{1}{4}$ sec. cor. of sec. 35, with brass
			cap marked
			½ S35
			1922
			Raise a mound of stone, 2 ft. base, 1 ft. high, N. of cor.
			Ascent of 115 ft. over rolling land to
		79 • 38	Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in
-	0		the ground, for the cor. of secs. 34 and 35, with
		• • •	brass cap marked T32N R29E
			s34 s35
	× 1		731N
			1922
			Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
			Land, gently rolling to rolling. Soil, sandy and rocky.
			Timber, none. Undergrowth, sage.
		and the second	
	0		From the cor. of secs. 34 and 35
			West, on S. bdy. of sec. 34
		•	Ascend gentle E. slope 65 ft. to 4 sec. cor.
	15%	17.00	Dry wash, drains NE.
	To the state of th	40.00	Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in
		and the state of t	the ground to solid rock, over a marked stone(x), in a
	The second secon		mound of stone, for $\frac{1}{4}$ sec. cor. of sec. 34, with brass
	The state of the s		cap marked ± s34
	0	*	1922
1			