

## SURVEY OF PORTION OF S. BDY. T. 32 N., R. 29 E.

CHAINS	West, on S. bdy. of sec. 32
	Ascend SE. slope 245 ft. to
19.30	Spur, projects N. Descend NW. slope 225 ft. to
38.60	Draw, drains N. Ascend
40.00	Set an iron post, 3 ft. long, 1 in. in dia., 16 ins. in the ground to solid rock, over a marked(x)stone, in a mound of stone, for $\frac{1}{4}$ sec. cor. of sec. 32, with brass cap marked
	$\frac{1}{4}$ S32
	1922
	Ascend NE. slope 55 ft. to
54.00	Spur, projects N. Descend W. slope 30 ft. to
57.00	Draw, drains NE. Ascend E. slope
58.20	Trail, bears N. and S.
66.20	Wire fence, bears NE. and SW.
74.20	Ridge, bears NE. and SW., 430 ft. above draw.
	Descend steep rocky W. slope 375 ft. to
80.00	Set an iron post, 3 ft. long, 2 ins. in dia., 8 ins. in the ground to solid rock, over a marked(x)stone, in a mound of stone, for the cor. of secs. 31 and 32, with brass cap marked
	T32N R29E
	S31   S32
	T31N
	1922
	Land, mountainous. Soil, rocky.
	Timber, scattering juniper. Undergrowth, sage.
	West, on S. bdy. of sec. 31
	Descend rocky NW. slope 335 ft. to creek
6.50	Road, bears NE. and SW.
7.50	Creek, course NE., 1 lk. wide, 2 ins. deep.
	Ascend E. slope 345 ft. to
33.10	Ridge, bears NE. and SW. Descend NW. slope 70 ft. to
40.00	Set an iron post, 3 ft. long, 1 in. in dia., 12 ins. in the ground, to solid rock, over a marked(x)stone, in a mound of stone, for $\frac{1}{4}$ sec. cor. of sec. 31, with brass cap marked