

SURVEY OF NORTH BOUNDARY OF T. 32 N., R. 29 E.

CHAINS

Land, gently rolling to level. Soil, sandy.
 Timber, none. Undergrowth, greasewood and shadscale.

S 89° 57' W., on true N. bdy. of sec. 6

Over rolling land

30.30 Drv wash, drains NE.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., of sec. 6, with brass cap marked

$\frac{1}{4}$ S6
1922

78.20 Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor. The cor. of Tps. 32 and 33 N., Rs. 28 and 29 E., hereinbefore described

Land, gently rolling. Soil, sandy.

Timber, none. Undergrowth, greasewood, shadscale and sage.

ESTABLISHMENT OF CORS. ON E. BDY. T. 32 N., R. 29 E.

At a point 64 lks. N. of the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, which is a 1 in. iron post, firmly set in the ground, and marked and witnessed as described by the Surveyor General, on which I change markings to refer to Sec. 31 only and move mound of stone to E. of cor.

Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in the ground to solid rock, over a marked(x) stone, in a mound of stone, for $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap marked

$\frac{1}{4}$ |
S36 |
1922

At a point 64 lks. N. of the cor. of secs. 25, 30, 31 and 36, which is a 3 in. iron post, firmly set in the ground, and marked and witnessed as described by the Surveyor General, on which I change markings to refer to secs. 30 and 31 only, and move mound of stone to E. of cor.