

## ESTABLISHMENT OF CORRS. ON E. BDY. T. 32 N., R. 29 E

CHAINS

Surveyor General; on which I change markings to refer to secs. 6 and 7 only, and place mound of stone E. of cor. Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground, for the cor. of secs. 1 and 12 only, with brass cap marked

T32N	
R29E	R30E
S1	S6
S12	S6

1922

Dig pits one in each section SW. and NW. of cor.

At a point 64 lks. N. of the  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, which is a 1 in. iron post, firmly set in the ground, and marked and witnessed as described by the Surveyor General, on which I change markings to refer to sec. 6 only, and dig pits crosswise on line N. and S. of cor. Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 1 only, with brass cap marked

$\frac{1}{4}$	
S1	

1922

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

SUBDIVISIONS T. 32 N., R. 29 E.

From the cor. of secs. 35 and 36, <sup>on S. bdy of twp.</sup> hereinbefore described N 0° 01' W., bet. secs. 35 and 36

Over gently rolling land

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$	
S35	S36

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

48.10 Dry wash, drains NE.

64.80 Old road, bears E. and W.