DEPENDENT RESURVEY OF SECTION 1, T 28 N., R. 33 E.

CHAINS	
	West, from ¼ sec. cor. with continuous measurement
86.04	Fall 25 lks. N. of the cor. of secs. 1, 2, 35 and 36, hereinafter described
	The bearing of this ½ mile is therefore S 89° 38' W., and the dist. 39.22 chs.

	From the cor. of secs. 1, 2, 35 and 36
	South, on retracement line bet. secs. 1 and 2
36.89	Fall 95 lks. E. of the old ¼ sec. cor., hereinafter described
	The bearing of this ½ mile is therefore S 1° 29' W., and the dist. 36.90 chs.
	South from ¼ sec. cor. with continuous measurement
76.75	Fall 37 lks. W. of the cor. of secs. 1, 2, 11 and 12, hereinafter described
	The bearing of this ½ mile is therefore S 0° 32' E., and the dist. 39.86 chs.

	From the cor. of secs. 1, 2, 11 and 12
	East, on retracement line bet. secs. 1 and 12
39.94	Fall 36 lks. S. of old ¼ sec. cor., hereinafter described
	The bearing of this ½ mile is therfore N 89° 29' E., and the dist. 39.94
	East from ¼ sec. cor. with continuous measurement
87.05	Fall 41 lks. S. of the cor. of secs. 1, 6, 7 and 12, hereinbefore described
	The bearing of this ½ mile is therefore N 89° 30' E., and the dist. 47.11 chs.

	From the cor. of secs. 1, 6, 7 and 12
	North, on resurvey line on E. bdy. of sec. 1
.75	Bottom of Limerick Canyon, no water, spring about 4 chs. W., drains W. Ascend SW. slope 204 ft. to
28.00	Draw, drains SW. Ascend along SE. slope 135 ft.
28.35	Frame cabin on line.
28.59	Intersect S. bdy. of Cape Horn Fraction N 79° 51' E., 2.65 chs. from Cor. No. 3, hereinafter described