

DEPENDENT RESURVEY OF SECTION 1, T. 28 N., R. 33 E.

CHAINS Timber, none. Undergrowth, sage.

S 89° 36' W., on resurvey line on N. bdy. of sec. 1
 Descend rocky SW. slope 480 ft. to
 27.80 Ravine, drains NW. Ascend NE. slope 40 ft. to
 30.75 Spur, projects N. Descend rocky NW. slope 210 ft. to
 35.15 Same ravine, drains SW. Ascend SE. slope 145 ft. to
 43.60 Rocky spur, projects S. Descend SW. slope 165 ft. to
 46.82 Old $\frac{1}{4}$ sec. cor., which is a stone firmly set in a mound
 of stone, marked and witnessed as described by the
 Surveyor General, alongside which I
 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$	S36
S1	

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high N. of cor.
 Thence
 S 89° 38' W., on N. bdy. of sec. 1, with continuous
 measurement
 Descend
 66.30 Ascend SE. slope 65 ft. to
 72.70 Spur, projects S. Descend SW. slope 375 ft. to
 86.04 The cor. of sec. 1, 2, 35 and 36, which is a stone firmly
 set in a mound of stone, and marked and witnessed as
 described by the Surveyor General, alongside which I
 Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in
 the ground, for the cor. of secs. 1, 2, 35 and 36, with
 brass cap marked

T29N R33E	
S35	S36
S2	S1
T28N	
1922	

Raise amount of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
 Land, mountainous. Soil, rocky.
 Timber, none. Undergrowth, sage.

S 1° 29' W., on resurvey line bet. secs. 1 and 2