

ESTABLISHMENT OF CORNERS ON E. BDY. OF T. 29 N., R. 39 E.

CHAINS At a point 2.25 chs. S. of the $\frac{1}{4}$ sec. cor. of secs. 31 and 36, on E. bdy. of twp., which is a 1 in. iron post, firmly set in the ground, and marked and witnessed as described by the Surveyor General, on which I change markings to refer to sec. 31 only and move mound of stone to E. of cor.

Set an iron post, 3 ft. long, 1 in. in dia., 16 ins. in the ground to solid rock, over a marked(x)stone, in a mound of stone, for $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap marked

$\frac{1}{4}$
 S36
 1922

At a point 2.25 chs. S. of the cor. of secs. 25, 30, 31 and 36, on E. bdy. of the twp., which is a 3 in. iron post, firmly set in a mound of stone, and marked and witnessed as described by the Surveyor General, on which I change markings to refer to secs. 30 and 31 only and move mound of stone to E. of corner.

Set an iron post, 3 ft. long, 2 ins. in dia., 16 ins. in the ground to solid rock, over a marked(x)stone, in a mound of stone, for the cor. of secs. 25 and 36, with brass cap marked

T29N
 R39E R40E
 S25
 S36 | S31
 1922

At a point 2.25 chs. S. of the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, on E. bdy. of twp., which is a 1 in. iron post, firmly set in the ground, and marked and witnessed as described by the Surveyor General, on which I change markings to refer to sec. 30 only and move mound of stone to E. of cor.