

SUBDIVISIONS T. 29 N., R. 39 E.

CHAINS From the cor. of secs. 35 and 36, on S. bdy. of the twp., which is a 3 in. iron post, firmly set in the ground, and marked and witnessed as described by the Surveyor General

Thence

N 0° 01' W., bet. secs. 35 and 36


Descend N. slope over rolling mountainous land 130 ft. to

8.00 S. Fork of Bushee Creek, 3 lks. wide, 2 ins. deep, course W. Ascend 85 ft. to

13.50 Low spur, projects W. Descend.

17.50 Draw, drains W. Ascend SW. slope 255 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked




Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Ascend 150 ft. to

48.90 Spur, projects SW. Descend NW. slope 215 ft. to

63.30 Ravine, drains W. Ascend 290 ft. to

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground, for the cor. of secs. 25, 26, 35 and 36, with brass cap marked



Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling mountainous. Timber, none.

Soil, rocky sand. Undergrowth, sage.

East, on a random line bet. secs. 25 and 36

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.18 Fall 2 lks. N. of the cor. of secs. 25 and 36, on E. bdy. of twp., hereinbefore described

Thence