

## SUBDIVISIONS T. 29 N., R. 39 E.

## CHAINS

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 16 ins. in the ground to solid rock, over a marked(x)stone, in a mound of stone, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
S15 | S14  
1922

Ascend 20 ft. to

42.20 Ridge, bears E. and W. Descend NW. slope 920 ft. to

69.00 Bottom of canyon, drains SW. Ascend steep rocky S. slope 250 ft. to

79.77 Intersect dependent resurvey bdy. 2.26 chs. S 89° 49' W. of the cor. of secs. 10 and 11, hereinbefore described

Set an iron post, 3 ft. long, 2 ins. in dia., 8 ins. in the ground to solid rock, over a marked(x)stone, in a mound of stone, for the closing cor. of secs, 14 and 15, with brass cap marked

T29N R39E  
S10  
S15 | S14  
C C  
1922

Land, rough mountainous. Soil, rocky.

Timber, none. Undergrowth, sage.

---

From the cor. of secs. 33 and 34, on S. bdy. of the twp., which is a 3 in. iron post, firmly set in the ground, and marked and witnessed as described by the Surveyor General

Thence

N 0° 02' W., bet. secs. 33 and 34

Descend NW. slope over mountainous land 405 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked