

Order of Procedure, cont.

Chains

and corners referring to sections 6 and 18 were established at 40.00 chs. latitude from the closing cor. of secs. 6 and 7 and of 7 and 18 respectively. The south bdy. of secs. 16, 17 and 18 was dependently resurveyed.

RESURVEY OF A PORTION OF THE SUBDIVISIONS OF FRACTIONAL
T. 31 N., R. 41 E.

From the cor. of secs. 9, 10, 15 and 16, which is an iron post, 2 ins. diam., properly marked, and firmly set in a mound of stone, and with a mound of stone to the west,

South, on retracement line, bet. secs. 15 and 16,

40.00 No trace of the original $\frac{1}{4}$ sec. cor. Set temp. point.

80.22 Fall 72 lks. E. of the old cor. of secs. 15, 16, 21 and 22. The true course of this line is N. 0°31'E., and the proportionate length of each half mile is 40.11 chs.

The old cor. of secs. 15, 16, 21 and 22, was marked by a decayed fragment of a willow stake about 30 ins. in length with distinct scribing on three faces, lying on a small but unmistakable mound of earth. No pits were evident. In the center of this mound of earth, set an iron post, 3 ft. long, ^{2 ins. diam.} 28 ins. in the ground, with brass cap marked

T31N	R41E
S 16	S 15
+	
S 21	S 22
1925	

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of
cor.

From the above cor.,

N. 0°31'E., on true line, bet. secs. 15 and 16,

Over gentle rolling land covered with a medium heavy undergrowth of shadscale and sagebrush and much surface rock.

2.00 Shallow dry wash, course S.85°E.

17.50 Old road, bears N.10°W. and S. 10°E.