

SURVEY OF A PORTION OF THE SUBDIVISIONS OF T. 31 N., R. 41 E.

Chains

side of rocky spur. Spur, about 2 chs. S., projects East.

70.40 Slope changes to a very steep, rocky NE.

82.14 Intersect the W. bdy. of Tp., 820 ft. above main draw, N.0°02'W., 68 lks. from the old cor. of secs. 7 and 18, which is an iron post, 3 ins. diam., firmly set, projecting 16 ins. above the ground, with markings on brass cap changed to the following:

A P
1925

and

N. 0°02'W., 1.41 chs. dist. from the cor. of secs. 12 and 13, which is an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, properly marked and witnessed.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to solid rock and 12 ins. in a mound of stone, 2 ft. base, for the closing cor. of secs. 7 and 18, with brass cap marked

T31N	
R40E	R41E
S 12	S 7 C S 18
1925	

Raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor. This cor. stands on crest of rocky spur, projecting SE. about 8 chs. thence N. of E. and S. of E.

Land, E. half mile; rolling and broken. W. half mile; very rough and choppy mountainous.

Soil, shallow rocky loam, rock subsoil, 3rd and 4th rate.

Undergrowth, sagebrush, buck brush, service berry.

No timber, Good grazing.

From the cor. of secs. 7, 8, 17 and 18,

N.0°01'W., on true line, bet. secs. 7 and 8,

Over rolling and broken hilly land thru medium dense