

SURVEY OF A PORTION OF THE SUBDIVISIONS OF T. 31 N., R. 41 E.

Chains

40.00 On steep N. slope 220 ft. above creek bottom,
Set an iron post, 3 ft. long, 1 in. diam., 4 ins. in the
ground over a cross (X) cut on bedrock, and in a
mound of stone, 3 ft. base, 2 ft. high, for the $\frac{1}{4}$ sec.
cor. of sec. 6 only, with brass cap marked

$\frac{1}{4}$ S 6

1925

40.76 Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the
ground to solid rock and 16 ins. in a mound of stone,
3 ft. base, for the $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S 7

1925

Continue ascent of steep NE. slope.

44.70 Spur, projects N., continue ascent of broken NE. slope.

58.00 Spur, 320 ft. above $\frac{1}{4}$ sec. cor., projects N., desc. 60ft
over broken W. slope.

60.90 Dry wash, course N., asc. broken NE. slope 380 ft.

82.90 Intersect the W. bdy. of Tp., N.0°02'W., 46 lks. distant
from the old cor. of secs. 6 and 7, which is an iron
post, 3 in. diam., firmly set, witnessed by a mound
of stone to the west. I change markings on brass cap
as follows and remove mound of stone.

A P

1925

At point of intersection, set an iron post, 3 ft. long,
2 ins. diam., 24 ins. in the ground, for the closing
cor. of secs. 6 and 7, with brass cap marked

T31N	R41E
R40E	S 6
S 1	C
	C
	S 7
	1925

Raise a mound of stone, 3 ft. base, 2 ft. high, E. of
cor. From this cor., the old cor. of secs. 1 and 12,
R. 40 E., which is an iron post, 2 ins. diam., firmly
set, properly marked and witnessed, bears S.0°02'E.,
1.14 chs. distant.