

Survey of the Sixth Standard Parallel North through a  
portion of range 58 east.

Chains. From the standard cor. of T. 31 N., Rs. 58 and 59 E.,  
which is an iron post, 3 ins. in diam., firmly set and  
properly marked and witnessed, as described in the field  
notes of T. 31 N., R. 59 E.,  
West, on a true line, on the S. Bdy. of sec. 36.  
Asc. rocky NE. slope 680 ft over mountainous land,  
through scattering timber and undergrowth. to  $\frac{1}{4}$  sec. cor.  
25.40 Enter dense clump of aspen, bears N. and S.  
32.70 Leave dense aspen clump, bears NE. and SW.  
40.00 Set an iron post, 3 ft. long, 1 in. in diam., 12 ins. in  
the ground, to solid rock, in a mound of stone, for the  
standard  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$$\begin{array}{r} S\ C \\ \frac{1}{4} S36 \\ \hline 1924 \end{array}$$

from which

A mahogany 6 ins. in diam., bears N.  $16^{\circ}$  E., 93 lks.  
distant, marked SC  $\frac{1}{4}$  S36 BT

A mahogany 5 ins. in diam., bears N.  $7\frac{1}{2}^{\circ}$  W., 56 lks.  
distant, marked SC  $\frac{1}{4}$  S36 BT

Asc. rocky NE. slope 130 ft.

45.20 Top of ridge with granite outcroppings, bears SE. and NW.

48.00 Top of ridge, bears NE. and SW. Desc. rocky NW. slope  
540 ft. through scattering mahogany and undergrowth.

74.60 Creek with running water, 3 lks. wide, 2 ins. deep,  
course SE. Asc. E. slope of spur 60 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 12 ins.  
in the ground, to solid rock, in a mound of stone, for  
the standard cor. of secs. 35 and 36, with brass cap mkd.

$$\begin{array}{r} S\ C \\ T31N\ R58E \\ S35\ S36 \\ \hline 1924 \end{array}$$

At base of post deposit a granite stone, 8 x 4 x 3 ins.,  
marked with cross (x). Raise a mound of stone, 2 ft.  
base,  $1\frac{1}{2}$  ft. high, N. of the cor. No bearing trees  
available.

Land, mountainous.

Soil, gravelly and rocky loam, 2nd and 3rd rate.