

Dependent resurvey of a portion of the E. Bdy. of T. 30 N., R. 58 E.

Chains

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

The corner stands on a rocky NE. slope.

Land, rolling and broken. Soil, rocky and gravelly.

Undergrowth, sage and buck brush. No timber.

Survey of a portion of the E. bdy. of T. 30 N., R. 58 E.

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy.

of the township,

North, on a true line, bet. secs. 13 and 18.

Desc. 40 ft. over rocky NE. slope of rolling land.

2.60 Dry wash, drains S.60°E., asc. 180 ft. over broken S. slope.

20.00 No trace of the original 1/16 section corner.

32.80 Dry wash, drains SE., asc. 70 ft. over S. slope.

40.00 On rocky SE. slope of spur, set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for the ¼ sec. cor. with brass cap mkd

S13	S18
-----	-----

1924

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of

cor. Asc., 50 ft. over SE. slope, thru medium

dense undergrowth.

44.90 Slope changes to NE., asc. 130 ft.

57.20 Dry wash, drains SE., asc. SW. slope 390 ft. over

numerous granite outcroppings.

73.00 Top of rocky spur, projects SE.

78.20 Top of spur, projects SE., desc. NE. slope 30 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in

the ground, for the cor. of secs. 7, 12, 13, and 18,

with brass cap mkd

T30N	
R58E	R59E
S12	S7
S13	S18

S12	S7
-----	----

S13	S18
-----	-----

1924

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.