

Survey of a portion of the E. Bdy. of T. 30 N., R. 58 E.

Chains.

From sec. cor., SE. cor. of mill building bears N. 48°
 $13'$ W.; cabin bears N. 44° W.; loading shoot bears
 N. $60^{\circ} 52'$ W.

Land, mountainous.

Soil, shallow gravelly and rocky loam, 3rd rate.

Undergrowth, sage and buckbrush.

Timber, aspen

 North, on a true line, bet. secs. 1 and 6.

Desc. N. slope 330 ft. over mountainous land.

19.70 Creek, course SE., 10 lks. wide, 6 ft. deep.

21.90 Road, bears E. and W. Asc. 180 ft. to change of slope.

23.10 Road, bears E. and W.

29.40 Desc. N. slope.

32.10 Dry wash drains SE. Asc. 100 ft. along center of wash.

40.00 In center of wash, set an iron post, 3 ft. long, 1 in.
 in diam., 12 ins. in the ground, to solid rock, in a
 mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S1 | S6
 1924

from which

A mahogany 7 ins. in diam., bears S. 43° E., 155 lks.

distant, marked $\frac{1}{4}$ S6 BT

A mahogany 9 ins. in diam., bears S. $45\frac{1}{2}^{\circ}$ W., 110 lks.

distant, marked $\frac{1}{4}$ S1 BT

Leave wash and Asc. S. slope 750 ft. through scattering
 mahogany and dense undergrowth, over granite outcropp-
 ings.

70.00 Top of spur-ridge, projects E. from W. Desc. NE. slope
 340 ft. through scattering timber.

79.84 Intersect the Sixth Standard Parallel North, at a point,
 West, 12.96 chs. distant, from the standard cor. of
 T. 31 N., Rs. 58 and 59 E.

At the point of intersection, set an iron post, 3 ft.
 long, 3 ins. in diam., 28 ins. in the ground, for the