

Dependent resurvey of a portion of the S. Bdy. of

T. 30 N., R. 58 E.

Chains.

Land, slightly rolling.

Soil, sandy to gravelly loam, 1st to 3rd rate.

Undergrowth, sage, willows, buckbrush.

Timber, scattering aspen and cottonwood along dry wash.

-----  
Survey of a portion of the S. Bdy. of T. 30 N., R. 58 E.  
-----

From the cor. of secs. 2, 3, 34 and 35, on the S. Bdy. of  
the township,

West, on a true line, on the S. Bdy. of sec. 34.

Asc. E. slope 30 ft. over rolling land.

10.00 Top of spur, projects SE. Desc. SW. slope 20 ft.

12.50 Dry wash, drains SE.

15.00 Ditch, 10 lks. wide, 4 ft. deep, drains SE. Asc. E. slope  
300 ft.

36.10 Top of spur, projects S. 80° E.

✓ 37.65 An easting of 200.00 chs. from the cor. of secs. 13, 18,  
19 and 24. Set an iron post, 3 ft. long, 1 in. in diam.,  
26 ins. in the ground, for the  $\frac{1}{4}$  sec. cor. of sec. 34,  
only, with brass cap mkd,

$\frac{1}{4}$  S34  
1924

from which

A mahogany 10 ins. in diam., bears N. 15 $\frac{1}{2}$ ° E., 170 lks.  
distant, marked  $\frac{1}{4}$  S34 BT

No other bearing tree available. Raise a mound of stone,  
2 ft. base, 1 $\frac{1}{2}$  ft. high, N. of the cor.

42.60 Desc. SW. slope 100 ft.

49.50 Dry wash, drains SE. Asc. 40 ft.

52.70 Dry wash, drains NE. Asc. E. slope 110 ft.

57.90 Top of spur, projects SE. Asc. 110 ft.

65.30 Top of spur, projects NE. Desc. gradual NW. slope.

75.30 Dry wash, drains NE. Enter grove of aspen, bears NE.  
and SW.

76.30 Leave aspen, bears NE. and SW. Asc. NE. slope 50 ft.

77.65 Set an iron post, 3 ft. long, 2 ins. in diam., 14 ins.