

Survey of a portion of the subdivisions of T. 30 N., R. 58 E.

Chains	
35.00	Top of rocky spur, projects S.60°E., desc. 30 ft. over precipitous NE. slope.
40.00	Near N. base of outcrops on NE. slope, Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock and 20 ins. in a large mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{1}{4}$ S3 S2 1925
	Deposit a granite stone, 8x6x4 ins., marked cross (x) at base of mound. This $\frac{1}{4}$ sec. cor. is set between two large granite boulders.
	Desc. 210 ft. over rocky NE. slope.
52.30	Rocky bottom of draw, drains N.70°E. 3 chs. thence S.60°E. Continue along rocky E. slope.
53.80	Main draw, drains S.60°E., asc. 940 ft. over precipitous S. slope thru dense undergrowth and scattering large limber pines, to corner.
61.85	Spring heads East 1.00 ch. distant., small stream flows SE. to main draw.
79.80	Intersect Sixth Standard Parallel North, West, 13.06 chs. distant from the Std. cor. of secs. 34 and 35, heretofore described.
	At point of intersection, which falls on granite outcrop extending about 10 ft. N. and S., 12 ft. E. and W., and about 3 ft. high, mark a cross (x) at exact corner point with 4 grooves W., 2 grooves E. and 6 grooves and CC S. of cross. Corner point is marked on south end of outcrop and about 1 ft. above ground surface. from which,
	A double limber pine, 36 ins. diam., bears S.82 $\frac{1}{2}$ °W.,
	35 lks. distant mkd T30N R58E S3 CC BT
	A limber pine, 5 ins. diam., bears S.30°W., 18 lks.
	distant, marked T30N R58E S3 CC BT
	Land, rough mountainous. Soil, shallow rocky loam, 4th. rate.
	Undergrowth, sage, laurel, willow.
	Timber, aspen, mahogany, limber pine.