

Resurvey of the W. bdy. of T. 22 N., R. 65 E.

Chains

	T22N	
R64E	R65E	
	S 6	
S 1	S 7	
	1924	

from which,

A pinon pine, 10 ins. diam., bears N. $51\frac{1}{2}^{\circ}$ E., 69 lks.
distant, marked T22N R65E S6 BT

A pinon pine, 10 ins. diam., bears S. $52\frac{1}{4}^{\circ}$ E., 51 lks.
distant, marked T22N R65E S7 BT

15.00 Small spur projects SW.

19.20 Draw drains SW.

40.31 The cor. of Ts. 22 and 23 N., R. 64 E., which is a 3 in.
iron post, firmly set alongside old scribed juniper
stake, marked and witnessed as described by the sur-
veyor general.

This corner was restored during the survey of T. 23 N.,
R. 65 E. in 1923 Group 102, Nevada.

Land, rolling and broken hilly.

Soil, shallow gravelly and rocky clay loam, medium to
coarse texture, 3rd rate.

Undergrowth, sagebrush, buck brush.

Timber, juniper, pinon pine.

Good grazing.

N. $0^{\circ}16'W.$, on true line, along the E. bdy. of sec. 36,
T. 23 N., R. 64 E.,

Over rolling and broken land thru heavy timber and medium
dense undergrowth. Asc. broken S. slope.

3.28 A northing of 40.00 chs. from the cor. of secs. 6 and 7,
Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the
ground, and 24 ins. in a mound of stone, 24 ins. high,
for the $\frac{1}{4}$ sec. cor. of sec. 6 only, with brass cap
marked