

Chains

pinon pine, cedar and mahogany.

N. 1° 09' E., on a true line along E. bdy. sec. 1.

Over rough mountainous land, through dense undergrowth,  
desc. over broken rocky NW. slope to

18.05 Ravine, 660 ft. below sec. cor., course N. 20° W.; con-  
tinue to descend over rocky NW. slope.

24.00 Enter dense timber, bears NW. and SE.

40.11 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the  
ground, for  $\frac{1}{4}$  cor. of sec. 1, with brass cap mkd.

$\frac{1}{4}$  S 1 |  
1923

From which.

A pinon pine, 12 ins. dia., bears N. 51° 08' W., 18 lks.  
dist., mkd.  $\frac{1}{4}$  S 1 B T.

A pinon pine, 16 ins. dia., bears S. 51° 25' W., 5 lks.  
dist., mkd.  $\frac{1}{4}$  S 1 B T.

This cor. stands on NW. slope 200 ft. below ravine; thence  
asc. SW. slope. 60 ft. to

52.10 Point of rocky spur, slopes N. 70° W.; desc. 70 ft. to

56.15 Gulch, course N. 80° W.; asc. 20 ft. to

58.75 Point of rocky spur, slopes W.; desc. 20 ft. to

60.35 Head of ravine, course W.; asc. abruptly 250 ft. over  
rocky SW. slope to

75.70 Top of rocky spur ridge, bears N. 70° W. and S. 70° E.;  
desc. 115 ft. to

80.22 Intersect the cor. of Tps. 23 and 24 N., Rs. 64 and 65 E.,  
heretofore described. I now change this cor. to a cor.  
common to Tps. 23 and 24 N., R. 64 E. only as follows:

At its original position,

Set an iron post, 3 ft. long, 3 ins. dia., 24 ins. in the  
ground, for cor. of Tps., 23 and 24 N., R. 64 E., with  
brass cap mkd.