

Survey of the S. Bdy. of T. 23 N., R. 65 E.

Chains.

with brass cap mkd.

T23N	R65E
S31	S32
S6	S5
T22N	
1922	

from which

a mahogany, 10 ins. in dia., bears N.84° E., 59 lks. dist., marked T 23 N R 65 E S 32 B T

a mahogany, 6 ins. in dia., bears S.36° E., 61 lks. dist., marked T 22 N R 65 E S 5 B T

a mahogany, 5 ins. in dia., bears S.87° W., 51 lks. dist., marked T 22 N R 65 E S 6 B T

a mahogany, 6 ins. in dia., bears N.11° W., 18 lks. dist., marked T 23 N R 65 E S 31 B T

Cor. stands on N.W. slope 500 ft. below summit of Schell Creek range.

Land, rough mountainous. Soil, rocky clay loam.

Undergrowth, medium growth of sage and bunch grass.

Timber, dense mahogany, pinon pine and cedar.

West, on a true line, bet. sees. 6 and 31.

Desc. N.W. slope over rough mountainous land, through dense mahogany, pinon pine and cedar timber.

29.00 Dry wash, 900 ft. below sec. cor., course S.W. Asc. S.E. slope.

35.00 Top of spur, 50 ft. above wash, projects S.W.

Desc. S.W. slope 50 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 12 ins. in the ground, to solid rock, in a mound of stone, for the 1/4 sec. cor., with brass cap mkd.

S31
1/4
S6
1922

from which

a pinon pine, 6 ins. in dia., bears N.51° E., 13 lks. dist., marked 1/4 S 31 B T

a cedar, 12 ins. in dia., bears S.21° E., 20 lks. dist., marked 1/4 S 6 B T