

Chains

West, on a true line bet. secs. 19 and 30.

Over rough mountainous land, through scattering timber and dense undergrowth, desc. 270 ft. over rocky SW. slope.

16.40 Ravine, with small stream of pure water, 1 lk. wide, 2 ins. deep, over rocky bottom, course S.; asc. 560 ft. to $\frac{1}{4}$ sec. cor.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 19
 $\frac{1}{4}$ —————
 S 30
 1922

From which

A pinon pine, 4 ins. dia., bears N. 29° 00' W., 22 lks. dist., mkd. $\frac{1}{4}$ S 19 B T.

A pinon pine, 4 ins. dia., bears S. 40° 30' W., 56 lks. dist., mkd. $\frac{1}{4}$ S 30 B T. Thence asc. 85 ft. to

44.20 Top of high, rocky ridge, bears N. and S. ; desc. abruptly 1005 ft. over rocky broken W. slope.

74.32 Intersect the E. bdy. of T. 23 N., R. 64 E., at a point, 1.97 chs. N. 1° 09' E. of the reestablished $\frac{1}{4}$ cor. of sec. 24, heretofore described. At the point of intersection,

Set an iron post, 3 ft. long, 2 ins. dia., 26 ins. in the ground, for closing cor. of secs. 19 and 30, with brass cap mkd.

T23N | T23N
 R64E | S19
 | S30 CC
 | R65E
 | 1922

From which

A balsam, 16 ins. dia., bears N. 81° 00' E., 1.25 chs. dist. mkd. CC T 23 N R 65 E S 19 B T.

A pinon pine, 16 ins. dia., bears S. 60° 40' E., 1.10 chs. dist., mkd. CC T 23 N R 65 E S 30 B T.

Land, rough mountainous. Soil, light sandy clay loam, medium texture dry shallow and mixed with loose granite