

Chains  
39.45 Top of spur, bears NW. and SE.; desc. 10 ft. to  
40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S. 18  
 $\frac{1}{4}$   
S. 19  
1922

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N.  
of cor.

Thence desc. abruptly over rocky SW. slope 445 ft. to  
58.45 Ravine, with a small stream of pure water, 1 lk. wide,  
 $\frac{1}{2}$  ins. deep, course NW.; asc. 40 ft. to spur.  
Enter dense timber, bears NW. and SE.

61.10 Point of spur slopes N.; desc. 95 ft. to  
66.70 Ravine, course N.; asc. 20 ft. to  
71.75 Point of spur, projects N.; desc. 25 ft. to  
72.33 Intersect the E. bdy. of T. 23 N., R. 64 E., at a point,  
1.70 chs.. N.  $1^{\circ} 09'$  E. of the reestablished  $\frac{1}{4}$  cor. of  
sec. 13, previously described. At the point of inter-  
section, which falls on a solid granite rock outcrop-  
ping, chisel a cross (X), over which,  
Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in a  
mound of stone, for closing cor. of secs. 18 and 19,  
with brass cap mkd.

T23N	T23N
R64E	S18
S13	S19-CC
	R65E
	1923

From which

A pinon pine, 16 ins. dia., bears N.  $59^{\circ} 20'$  E., 28 lks.  
dist., mkd. CC T 23 N R 65 E S 18 B T.

A pinon pine, 17 ins. dia., bears S.  $31^{\circ} 30'$  E., 59 lks.  
dist., mkd. CC T 23 N R 65 E S 19 B T.

Land, rough mountainous. Soil, light sandy clay loam,  
mixed with coarse gravel and decomposed granite and  
loose boulders; much sliderock and limestone rock out-  
croppings. Undergrowth, sagebrush, buckbrush, cherry  
brush and a fine growth of nutritious grasses. Timber,  
Mahogany, pinon pine and cedar.