

Subdivisions of T. 23 N., R. 65 E.

97

Chains

West, on a true line bet. secs. 6 and 7.

Over rough mountainous land, through scattering timber and dense undergrowth, asc. 70 ft. to

3.95 Top of divide ridge of Schell Creek Range, bears NE. and SW.; desc. 135 ft. to

13.65 Gulch, course N.; asc. 135 ft. to

25.15 Top of spur, bears N. 20° W., and S. 20° E.; desc. 135 ft.

34.95 Ravine, course N.; asc. 130 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the ground to solid rock and 14 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 6

 $\frac{1}{4}$ S 7
1922

From which

A pinon pine, 6 ins. dia., bears N. 54° 00' E., 1.18 chs. dist., mkd. $\frac{1}{4}$ S 6 B T.A pinon pine, 6 ins. dia., bears S. 5° 00' E., 80 lks. dist., mkd. $\frac{1}{4}$ S 7 B T.56.90 Top of rocky spur ridge, 315 ft. above $\frac{1}{4}$ sec. cor., bears N. and S.; desc. 300 ft. to69.08 Intersect the E. Bdy. of T. 23 N., R. 64 E., at a point, 1.25 chs. N. 1° 09' E., from the reestablished $\frac{1}{4}$ cor. of sec. 1, heretofore described. At the point of intersection,

Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for closing cor. of secs. 6 and 7, with brass cap mkd.

T23N	T23N
R64E	S 6 CC
S 1	S 7
	R65E
	1923

From which

A pinon pine, 16 ins. dia., bears N. 21° 51' E., 1.30 chs., dist., mkd. CC T 23 N R 65 E S 6 B T.

A pinon pine, 24 ins. dia., bears S. 75° 15' E., 19 lks. dist., mkd. CC T 23 N R 65 E S 7 B T.