

## Subdivisions of T. 25 N., R. 66 E.

47

Chains													
43.00	Point of low spur, projects NW.												
47.80	Gulch, course N. 70° W.; asc.												
48.52	Intersect the 5th Standard Parallel North, at a point, 11.70½ chs. S. 89° 07' E., from the reestablished standard ¼ cor. of sec. 35, heretofore described. At the point of intersection, Set an iron post, 3 ft. long, 2 ins. dia., 26 ins. in the ground, for closing cor. of secs. 2 and 3, with brass cap mkd.												
	<table style="margin: auto;"> <tr><td>T26N</td><td>R66E</td></tr> <tr><td>S35</td><td></td></tr> <tr><td>S 3</td><td>S 2</td></tr> <tr><td>T25N</td><td>R66E</td></tr> <tr><td>C</td><td>C</td></tr> <tr><td>1923</td><td></td></tr> </table>	T26N	R66E	S35		S 3	S 2	T25N	R66E	C	C	1923	
T26N	R66E												
S35													
S 3	S 2												
T25N	R66E												
C	C												
1923													
	Dig pits, 18x18x12 ins., crosswise on each line, E. W. and S. of post, 3 ft. dist.												
	Land, rolling, Soil, light sandy clay loam, mixed with coarse gravel and decomposed limestone dry shallow and rocky; 3rd rate. Undergrowth, sagebrush, greasewood and a scant growth of grass. Timber, scrub pinon pine and juniper.												
	-----												
	From the closing cor. of secs. 2 and 3, on the 5th Stan- dard Parallel North, S. 89° 07' E., on a blank line along N. Bdy. of sec. 2.												
28.84	The reestablished standard cor. of secs. 35 and 36.												
39.98½	Point for ¼ sec. cor. for sec. 2, midway bet. closing cors. for secs. 1 and 2, and 2 and 3, at which point, Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for ¼ cor. of sec. 2, with brass cap mkd.												
	<table style="margin: auto;"> <tr><td>¼ S 2</td></tr> <tr><td>1923</td></tr> </table>	¼ S 2	1923										
¼ S 2													
1923													
	and raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.												
69.38½	The reestablished standard ¼ cor. of sec. 36.												
79.97	The closing cor. of secs. 1 and 2.												
	-----												