Chains	
	dig pits, 18x18x12 ins. N. and S. of post, 3 ft. dist. thence desc. 15 ft. to
51.98	Intersect the 5th Standard Parallel North, at a point, 14.79½ chs., S. 89° 07' E., from the reestablished standard ¼ cor. of sec. 32, heretofore described. At the point of intersection,
	Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground, for closing cor. of secs. 5 and 6, with brass cap, mkd.

T26N R66E
S32
S 6 | S 5
T25N | R66E
C | C
1923

	and raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.
	Land, rolling. Soil, light sandy clay loam, medium texture, mixed with coarse gravel, 3rd rate. Undergrowth, sagebrush and a scant growth of grass. No timber.

	From the closing cor. of secs. 5 and 6, on the 5th Standard Parallel North,
	S. 89° 07' E., on a blank line along N. bdy. of sec. 5.
25.75	The reestablished standard cor. of secs. 32 and 33.
40.06	Point for ¼ cor. of sec. 5, midway bet. closing cors. for secs. 5 and 6 and 4 and 5, at which point,
	Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the ground, for ¼ cor. of sec. 5, with brass cap mkd.

¼ S 5
1923

	dig pits, 18x18x12 ins., E. and W. of post, 3 ft. dist.
66.29½	The reestablished standard ¼ cor. of sec. 33.
80.12	The closing cor. of secs. 4 and 5.

	From the closing cor. of secs. 5 and 6, on the 5th Standard Parallel North,
	N. 89° 07' W., on a blank line along N. bdy. of sec. 6.