

Dependent Resurvey of the 5th Stand. Par. N. through
a portion of Rs. 67 and 68 E.

Chains.

S C
 $\frac{1}{4}$ S31
1922

- 40.90 Dig pits, 18 x 18 x 12 ins., E. and W. of post, 3 ft. dist.
Thence East on true line on South Bdy. of sec. 31.
Dry wash, 10 ft. below $\frac{1}{4}$ sec. cor., course S.
Asc. S.W. slope.
- 43.90 Top of low spur, 10 ft. above wash, projects S.
Desc. S.E. slope 50 ft. to
- 79.90 Intersect the old stand. cor. of secs. 31 and 32, which
is a cedar post, 2 ft. long, 3 ins. square, marked 1
notch on W. face and 5 notches on E. face. All other
markings obliterated. Alongside, set an iron post, 3 ft.
long, 2 ins. in dia., 27 ins. in the ground, for the
stand. cor. of secs. 31 and 32, with brass cap mkd.

S C
T26N | R68E
S31 | S32
1922

Dig pits, 18 x 18 x 12 ins. N., E. and W. of post, 3 ft.
dist.

Land, rolling. Soil. sandy and rocky clay loam of medium
texture. Undergrowth, sage, shadscale and bunch grass.
No timber.

Survey of the E. Bdy. of T. 25 N., R. 67 E.

From the cor. of Ts. 24 and 25 N., Rs. 67 and 68 E.,
which is an iron post, 3 ins. in dia., described in the
field notes of the E. Bdy. of T. 24 N., R. 67 E., "book
A of this Group".

- North, on a true line, bet. secs. 31 and 36.
Asc. S.E. slope over rolling land, through scattering
cedar and pinon pine timber.
- 14.60 Top of spur, 30 ft. above twp. cor., projects N.E.
Desc. N.W. slope.
- 19.60 Dry wash, 30 ft. below spur, course N.E.
Asc. S.E. slope.
- 27.40 Top of spur, 10 ft. above wash, projects N.E.
Desc. N.W. slope.