

Survey of the E. Bdy. of T. 25 N., R. 67 E.

Chains

in the ground, for the cor. of secs. 1 and 6, 7 and 12,
with brass cap mkd.

T25N	
R67E	R68E
S1	S6
S12	S7
1922	

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of the cor.

Cor. stands on S.E. slope, 20 ft. above road.

Land, slightly rolling. Soil, sandy and rocky clay
loam. Undergrowth, sage, shadscale and bunch grass.

Timber, a few scattering cedar and pinon pine.

North, on a true line, bet. secs. 1 and 6.

Asc. S.E. slope over rolling land.

4.80 Top of spur, 10 ft. above sec. cor., projects E. from
N.W. Desc. N.E. slope.

34.80 Dry wash, 10 ft. below spur, course E.
Asc. S.E. slope.

39.50 Top of spur, 10 ft. above wash, projects E.
Desc. N.E. slope 10 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 27 ins.
in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
↑
S1 S6
↓
1922

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W.
of the cor.

42.40 Dry wash, 30 ft. below $\frac{1}{4}$ sec. cor., course E.
Asc. S.E. slope 10 ft. to

44.64 Intersect the 5th Stand. Par. N., at a point, East, 6.22
chs. dist. from the stand. $\frac{1}{4}$ sec. cor. for sec. 31,
T. 26 N., R. 68 E., hereinbefore described.

Set an iron post, 3 ft. long, 3 ins. in dia., 27 ins.
in the ground, for the closing cor. of Ts. 25 N., Rs.
67 and 68 E., with brass cap mkd.