

Survey of the E. Bdy. of T. 25 N., R. 67 E.

Chains.

T26N	R68E
S31	

S1	S6
R67E	R68E
T25N	
C C	
1922	

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of the cor.

Land, slightly rolling. Soil, sandy and rocky clay loam.

Undergrowth, sage, shadscale and bunch grass.

Timber, a few scattering cedar and pinon pine.

Survey of the S. Bdy. of T. 25 N., R. 67 E.

From the cor. of Ts. 24 and 25 N., Rs. 67 and 68 E., hereinbefore described.

West, on a true line, bet. secs. 1 and 36.

Asc. S.E. slope over rolling mountainous land.

37.00 Top of spur, 170 ft. above twp. cor., projects S.70° E. Enter dense pinon pine and cedar timber.

Continue ascent along S.W. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S36	
$\frac{1}{4}$	
S1	
1922	

from which

a pinon pine, 6 ins. in dia., bears N.81 $\frac{3}{4}$ ° E., 33 lks. dist., marked $\frac{1}{4}$ S 36 B T

a pinon pine, 5 ins. in dia., bears S.10° E., 40 lks. dist., marked $\frac{1}{4}$ S 1 B T

Cor. stands on S.W. slope 20 ft. above spur.

58.40 Dry wash, 20 ft. above $\frac{1}{4}$ sec. cor., course S.E.

Asc. S.E. slope 180 ft. to

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 1 and 2, 35 and 36, with brass cap mkd.