

Survey of the S. Bdy. of T. 25 N., R. 67 E.

Chains.	West, on a true line, bet. secs. 5 and 32.										
	Desc. N.W. slope over rough mountainous land, through scattering pinon pine, cedar and mahogany.										
17.50	Dry wash, 110 ft. below sec. cor., course N.E.										
	Asc. N.E. slope.										
18.00	Road, 10 ft. above wash, bears S.W. and N.										
34.50	Top of ridge, 250 ft. above road, divide bet. Antelope and Spring valleys, bears N. and S.										
	Desc. S.W. slope 60 ft. to										
40.00	Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.										
	$\frac{1}{4} \frac{S32}{S5}$ 1922										
	and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of the cor.										
51.70	Dry wash, 200 ft. below $\frac{1}{4}$ sec. cor., course S.W.										
	Asc. S.E. slope.										
76.50	Top of spur, 300 ft. above wash, projects S.W.										
	Desc. N.W. slope 40 ft. to										
80.00	Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 5 and 6, 31 and 32, with brass cap mkd.										
	<table border="1"> <tbody> <tr> <td>T25N</td> <td>R67E</td> </tr> <tr> <td>S31</td> <td>S32</td> </tr> <tr> <td>S6</td> <td>S5</td> </tr> <tr> <td colspan="2">T24N</td> </tr> <tr> <td colspan="2">1922</td> </tr> </tbody> </table>	T25N	R67E	S31	S32	S6	S5	T24N		1922	
T25N	R67E										
S31	S32										
S6	S5										
T24N											
1922											
	and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.										
	Land, rough mountainous. Soil, rocky clay loam.										
	Undergrowth, sage, shadscale and bunch grass.										
	Timber, scattering mahogany, cedar and pinon pine.										
	West, on a true line, bet. secs. 6 and 31.										
	Desc. N.W. slope over rough mountainous land.										
14.70	Top of spur, 190 ft. below sec. cor., projects N.										
	Desc. N.W. slope.										
39.20	Dry wash, 310 ft. below spur, course S.W.										