

Subdivisions of T.25 N., R. 67 E.

Chains.

- 4.10 Top of spur, 40 ft. above sec. cor., projects W.
Desc. N.E. slope.
- 9.10 Dry wash, 40 ft. below spur, course W.,
Asc. S.W. slope.
- 25.50 Top of spur-ridge, 170 ft. above wash, bears E. and W.
Desc. N.W. slope.
- 39.50 Dry wash, 200 ft. below spur-ridge, course N.E.
Asc. S.E. slope 10 ft. to
- 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in
the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S4 \mid S3 \\ \mid \\ 1922 \end{array}$$

from which

a cedar, 6 ins. in dia., bears N. $4\frac{1}{2}^{\circ}$ E., 302 lks. dist.,
marked $\frac{1}{4}$ S 3 B T

a cedar, 5 ins. in dia., bears N. $29\frac{1}{2}^{\circ}$ W., 119 lks. dist.,
marked $\frac{1}{4}$ S 4 B T

Asc. S.E. slope 50 ft. to

- 46.79 Intersect the 5th Stand. Par. N., at a point, S. $89^{\circ} 38'$ E.,
6.365 chs. dist., from the stand $\frac{1}{4}$ sec. cor. of sec. 34.
Set an iron post, 3 ft. long, 2 ins. in dia., 17 ins.
in the ground, to solid rock, in a mound of stone, for
the closing cor. of secs. 3 and 4, with brass cap mkd.

$$\begin{array}{c} T26N R67E \\ \mid \\ S 34 \\ \mid \\ S4 \mid S3 \\ T25N \mid R67E \\ C \mid C \\ \mid \\ 1922 \end{array}$$

from which

a cedar, 6 ins. in dia., bears S. $39\frac{1}{2}^{\circ}$ E., 38 lks. dist.,
marked C C T 25 N R 67 E S 3 B T

a pinon pine, 6 ins. in dia., bears S. 77° W., 133 lks.
dist., marked C C T 25 N R 67 E S 4 B T

Land, rolling mountainous. Soil, sandy and rocky clay
loam of medium texture. Undergrowth, sage, shadscale
and bunch grass. Timber, pinon pine and cedar.