

Dependent Resurvey of the Boundaries of secs. 27, 34 and 35,

T. 22 N., R. 20 E.

21

Chains

- 39.85 Dim road, bears N. 20° E. and S. 25° W.
- 39.96 Intersect the $\frac{1}{2}$ sec. cor., which is a granite stone, 10x8x6 ins., above the ground, firmly set, mkd. and witnessed as described by the surveyor general. I reconstruct this cor. as follows: Alongside,
Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for $\frac{1}{2}$ sec. cor., with brass cap mkd.
- S 22

S 27
1924
- and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
- I now change my course to N. 89° 40' W., and continue with measurement. Desc. 25 ft.
- 46.10 Ravine, channel, 20 lks. wide, gravel bottom, with perpendicular banks 8 ft. high, course N.; asc. abruptly 270 ft. to
- 56.20 Top of spur, bears N. and S.; desc. 170 ft. to
- 67.50 Gulch, course SE.; desc. 15 ft. to
- 70.30 Point of spur, projects S. 10° E.; desc. 10 ft. to
- 73.80 Gulch, course S. 60° E.; asc. 10 ft. to
- 80.06 The cor. of secs. 21, 22, 27 and 28.

Land, mountainous and rolling mountainous.

Soil, light sandy clay loam, medium texture, dry and very rocky; 4th rate.

Undergrowth, sagebrush, buckbrush, greasewood, briars, shadscale and a fair growth of bunch grass.

A few scattering scrub juniper in the E. $\frac{1}{2}$ mile.

Survey of Copper King Lode.

Beginning at the Location monument which is an oak post, $2\frac{1}{2}$ ft. long, 4 ins. sq., firmly set in a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, with location notice attached. I mark the point further by a nail driven in the said post. Whence