

SURVEY OF PORTION OF E. BOUNDARY OF T. 31 N., R. 23 E.

CHAINS

SURVEY OF PORTION OF E. BOUNDARY OF T. 31 N., R. 23 E.

I begin at the cor, of secs. 1, 6, 31 and 36, Ts 31 and 32 N., Rs 23 and 24 E., which is an iron post, 3 ins. in dia., firmly set in the ground, and marked and witnessed as described by the Surveyor General.

Thence

South on true line bet. secs. 1 and 6


Descend gradual S. slope over rolling mountainous land.

2.50 Head of dry wash, drains W., 30 ft below cor., ascend N. slope.

19.30 Ridge, bears E. and W., 82 ft. above wash, desc. SW. slope.

32.20 Dry wash, drains N 80° W., 131 ft. below ridge, thence over rolling land.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked




Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.

Continue over rolling land

49.90 Dry wash, drains W.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground, for the cor. of secs. 1, 6, 7 and 12, with brass cap marked



No stone available; pits impracticable.

Land, rolling mountainous to rolling; soil sandy with rock outcropping; timber none; undergrowth, sage and shadscale.

South on true line bet. secs. 7 and 12

Over rolling land

15.00 Ascend 118 ft. N. slope to

21.00 Ridge, bears E. and W., desc. S. slope.