

SURVEY OF PORTION OF E. BOUNDARY OF T. 31 N., R. 23 E.

CHAINS
80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground, for the cor. of secs. 13, 18, 19 and 24, with brass cap marked

T31N
S13 | S18

S24 | S19
R23E R24E
1922

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor. Land, rolling. Soil, sandy and gravelly. Timber, none. Undergrowth, shadscale. General drainage W.

J. Lee

SURVEY OF A PORTION OF SUBDIVISIONS OF T. 31 N., R. 23 E.

From the cor. of secs. 13, 18, 19 and 24, on E. Bdy. of the Twp.

West on true line bet. secs. 13 and 24

Descend over gently rolling land

17.75 Dry wash, drains NW., 171 ft. below sec. cor.; thence over nearly level land.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$ S13

S24
1922

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Continue over level land.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 8 ins. in rocky ground over a marked stone, supported by a mound of stone, for the cor. of secs. 13, 14, 23 and 24, with brass cap marked

T31N R23E
S14 | S13

S23 | S24
1922

Land, gently rolling to level. Soil, sandy. Timber, none. Undergrowth, sage and shadscale.