

Survey of the West Boundary of T. 25 N., R. 45 E.

Chains 80.00	<p>Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 1, 6, 7 and 12, with brass cap mkd.,</p> <div><div>T25N</div><div>R44E R45E</div><div>S1 S6</div><div>S12 S7</div><div>1925</div></div> <p>at base of post deposit a granite stone 6 x 4 x 4 ins., marked with cross (X). No other accessories available. Land, slightly rolling. Soil, light sandy and gravelly clay. Undergrowth, medium growth of shadscale, rabbit-brush and sage; scant growth of grass. No timber.</p> <hr/>
1.00	Asc. over general SE. slope over slightly rolling land.
19.90	Road Austin to Beowawe, bears NE. & SW. Dry wash, course S. 40° E.
34.90	Dry wash, course S. 45° E.
40.00	<p>Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.</p> <div><div>$\frac{1}{4}$</div><div>S1 S6</div><div>1925</div></div> <p>at base of post deposit a granite stone 4 x 4 x 6 ins., marked with cross (X) No other accessories available.</p>
43.80	Ditch, course S. 50° E.
57.60	Dry wash, course S. 30° E.
61.60	Dry wash, course S.E.
71.10	Draw, course SE.
78.09	Dry wash, course S. 45° E.
82.40	Draw, course SE.
84.88	<p>Intersect 5th Stand. Par. North, at a point, East 6.82 chs. dist. from the Stand. $\frac{1}{4}$ sec. cor. for sec. 36, which is an iron post, 1 in. in diam., firmly set and properly marked and witnessed as described in the field notes of T. 26 N., R. 45 E. At point of intersection set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, for the closing cor. of T. 25 N., Rs.,</p>