

Survey of the East Boundary of T. 25 N., R. 45 E.

Chains

North, bet. secs. 7 and 12.

Asc. SE. slope 170 ft. to

29.40 Spur, projects SE. Descend gradually.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins.

in the ground for $\frac{1}{4}$ sec. cor., for sec. 12, with brass cap mkd.

$\frac{1}{4}$
S12
1925

raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high W. of cor.48.30 Dry wash, course SE. Asc. 215 ft. over SW. slope of spur, projects S. 10° W.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground for the cor. of secs. 1 and 12, with brass cap mkd.

T25N
T25N
R46E
S1
S12
R45E
1925

raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Land, rolling mountainous. Soil, sandy, gravelly and rocky clay. Undergrowth, sage, shadscale and fair growth of grass. Timber, scattering juniper.

North, bet. secs. 1 and 6

Ascend gradually.

5.00 Top of spur, projects SE. Asc. E. slope 25 ft. to

10.00 Top of ridge, bears E. and W. Desc. gradual N. slope.

19.50 Dry wash, course SE. Desc. gradual NE. slope.

26.80 Dry wash, course SE. Asc. SE. slope 85 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in the ground to solid rock and 18 ins. in a mound of stone, for $\frac{1}{4}$ sec. cor., for sec. 1, with brass cap mkd.,

$\frac{1}{4}$
S1
1925

at base of post deposit a granite stone, 8 x 8 x 4 ins.

marked with cross (X). No other accessories available. Descend gradually