

Survey of the Subdivisions of T. 25 N., R. 45 E.

Chains

the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 1
 $\frac{1}{4}$ ———
 S 12
 1925

raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high N.
 of cor. Spur projects SW. Desc. W. slope of spur,
 100 ft. to

48.70 Dry wash, course SW. Asc. gradually

53.70 Top of spur, projects S. Desc. SW. slope 170 ft. to

67.05 Dry wash, course SE. Small spring, bears $1\frac{1}{2}$ chs. NW.

Asc. NE. slope 30 ft. to

73.80 Top of ridge, bears SE. & NW. Desc. SW. slope 60 ft. to

80.28 The cor. of secs. 1, 2, 11 and 12.

Land, rough mountainous. Soil, rocky and gravelly clay.

Undergrowth, sage, good growth of grass. No timber.

N. $0^{\circ} 01'$ W. bet. secs. 1 and 2.

Asc. SW. slope of ridge 55 ft. to

6.90 Top of ridge, bears SE. and NW. Desc. NE. slope 35 ft. to

9.85 Dry wash, course SE. Asc. SW. slope of ridge 400 ft. to

$\frac{1}{4}$ sec. cor.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 20 ins.

in the ground, to solid rock, and 16 ins. in a mound

of stone, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S2 | S1
 1925

at base of post deposit a granite stone 6x5x8 ins.

marked with cross (X)

Ascend SW. slope 260 ft. to

55.50 Top of ridge, bears SW. and NE. Asc. SW. slope 200 ft.
 to

68.50 Top of ridge, bears E. and W. Desc. NW. slope 30 ft. to

70.50 Top of ridge, bears N. 80° W. and S. 80° E.

Descend abrupt NW. slope 335 ft. to

85.49 Intersect the Fifth Standard Parallel North, at a point

E., 4.06 chs. distant from the Std. $\frac{1}{4}$ sec. cor. of

sec. 35.