

Survey of the Subdivisions of T. 25 N., R. 45 E.

Chains

at base of post deposit a granite stone 12 x 6 x 5 ins., marked with cross (X) No other accessories available. Descend steep NE. slope 410 ft. to

60.79 Dry wash, course NW. Intermittent stream of water 2 lks. wide, 2 ins. deep. Asc. S. slope 100 ft. to

72.75 Top of spur, projects N. 75° W. Desc. N. slope 75 ft. to
85.56 Small spring bears N. 59° W. 21.00 chs. dist.

Intersect the Fifth Standard Parallel North, at a point E. 3.83 chs. distant from the Std. 1/4 sec. cor. of sec. 34

At point of intersection set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground for closing cor. of secs. 2 and 3, with brass cap mkd.

T26NR45E
S34
S3 S2
T25NR45E
CC
1925

raise a mound of stone, 3 ft. base, 1 1/2 ft. high S. of corner.

Land, rolling. Soil, light, gravelly, rocky clay.

Undergrowth, sage, shadscale and scant growth of grass.

No timber.

From the cor. of secs. 3, 4, 33 and 34, on the south boundary of the township, which is an iron post, 2 ins. in diam., firmly set and properly marked and witnessed as described in the field notes of T. 24 N., R. 45 E.

N. 0° 02' W. bet. secs. 33 and 34.

Over slightly rolling land.

9.70 Dry wash, course S. 80° W.

17.10 Dry wash, course N. 60° W.

20.40 Dry wash, course N. 70° W.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground for 1/4 sec. cor., with brass cap mkd.

S33 S34
1925

raise mound of stone, 3 ft. base, 1 1/2 ft. high W. of corner.

42.40 Dry wash, course N. 55° W.

47.10 Dry wash, course N. 60° W.