

Survey of the Subdivisions of T. 25 N., R. 45 E.

Chains	N. 89° 52' W., on a true line bet. secs. 3 and 10
3.00	Top of ridge, bears NE. and SW.
	Descend along W. slope 800 ft. to
39.99	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap mkd.
	<div style="text-align: center;"> $\frac{1}{4}$ <div style="display: inline-block; vertical-align: middle;"> S 3 <hr style="width: 50px; border: 0.5px solid black;"/> S 10 1925 </div> </div>
	raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high N. of corner.
	Descend along West slope 330 ft. to
79.98	The cor. to secs. 3, 4, 9 and 10.
	Land, rolling. Soil, light, gravelly, rocky clay.
	Undergrowth, sage, shadscale and scant growth of grass.
	No timber.
<hr style="border-top: 1px dashed black;"/>	
	N. 0° 02' W., bet. secs. 3 and 4.
	Ascend gradual SW. slope.
7.30	Dry wash, course W.
13.70	Dry wash, course S. 85° W.
25.00	Dry wash, course W.
37.35	Dry wash, course W.
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<div style="text-align: center;"> $\frac{1}{4}$ <div style="display: inline-block; vertical-align: middle;"> S4 S3 <hr style="width: 50px; border: 0.5px solid black;"/> 1925 </div> </div>
	raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high W. of corner. Over broken land.
51.20	Dry wash, course N. 70° W.
53.60	Top of spur, projects W.
54.20	Dry wash, course W.
56.90	Top of spur, projects W.
58.40	Dry wash, course S. 80° W.
66.00	Dry wash, course W.
71.90	Dry wash, course N. 25° W.
85.29	Intersect the Fifth Standard Parallel North, at a point
	E. 3.98 chs. distant from the Std. $\frac{1}{4}$ sec. cor. of sec. 33