

## Survey of the Subdivisions of T. 25 N., R. 45 E.

Chains

At point of intersection set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground for closing cor. of secs. 3 and 4, with brass cap mkd.

T26NR45E	
S33	
S4	S3
T25NR45E	
CC	
1925	

raise a mound of stone, 3 ft. base, 1½ ft. high S., of corner.

Land, rolling. Soil, light, gravelly, rocky clay.

Undergrowth, sage, shadscale and scant growth of grass.

No timber.

## Secs.

From the cor. of 4, 5, 32 and 33, on the south boundary of the township, which is an iron post, 2 ins. in diam., firmly set and properly marked and witnessed as described in the field notes of T. 24 N., R. 45 E N. 0° 03' W. bet. secs. 32 and 33.

Over slightly rolling land.

15.00 Dry wash, course N. 45° W.

40.00 Set an iron post, 3 ft. long, 1 in. in diam. 27 ins. in the ground for ¼ sec. cor., with brass cap mkd.

¼	
S32	S33
1925	

at base of post, deposit a granite stone 6 x 6 x 4 ins. marked with cross (X) No other accessories available.

40.20 Draw, course N. 55° W.

64.60 Dry wash, course N. 50° W.

77.75 Dry wash, course N. 45° W.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam. 27 ins. in the ground for the cor. to secs. 28, 29, 32 and 33, with brass cap mkd.

T25N R45E	
S29	S28
S32	S33
1925	

at base of post, deposit a granite stone 7 x 6 x 5 ins. marked with cross (X) No other accessories available.