

Retracement of the S. Bdy. of T. 27 N., R. 45 E.

Chains.

- ✓ The course of this $\frac{1}{2}$ mile is N. $89^{\circ} 19'$ W., and the distance is 40.51 chs.
- 80.07 Fall. 109 lks. S. of the old cor. of secs. 3, 4, 33 and 34, which is a granite stone, 16 x 13 x 9 ins., firmly set in a mound of stone, marked with 3 notches on E. and W. faces.
- ✓ The course of the W. $\frac{1}{2}$ mile is N. $89^{\circ} 07'$ W. and the distance is 39.56 chs.
-
- From the old cor. of secs. 3, 4, 33 and 34, West, on retracement, making diligent search for old cors. at 40.00 and 80.00 chs. No old corners were found, until a point
- 233.66 Fall 225 lks. N. of the cor. of Ts. 26 and 27 N., Rs. 44 and 45 E., which is an iron post, 3 ins. in diam., firmly set and properly marked and witnessed.
- ✓ The course of this line is S. $89^{\circ} 27'$ W., and the dist. is 233.66 chs.
-
- Dependent Resurvey of a portion of the S. Bdy. of
T. 27 N., R. 46 E.
-
- From the closing cor. of T. 26 N., Rs. 45 and 46 E., which is an iron post, 3 ins. in diam., firmly set, and properly marked and witnessed, as described in the field notes of T. 26 N., R. 46 E., S. $89^{\circ} 54'$ W., on a true line, previously surveyed, and recorded in the field notes of T. 27 N., R. 46 E.,
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 1, only, with brass cap mkd.
- SI
1925
- Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of the cor.
- 44.37 Intersect the cor. of T. 27 N., Rs. 45 and 46 E., herein-
before described.