

Independent Resurvey of a portion of the S. Bdy. of

T. 27 N., R. 45 E.

Chains. West, on a true line, on the N. Bdy. of sec. 6.
 Desc. SW. slope over broken mountainous land.
 2.30 Dry wash, course SE. Asc. NE. slope 430 ft.
 24.70 Top of spur, projects N. Desc. W. slope 170 ft.
 38.00 Dry wash, course NE.
 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins.
 in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 6, only,
 with brass cap mkd.

$\frac{1}{4}$ S6	✓
1925	

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, S. of the cor.

Asc. along S. slope 230 ft.

58.30 Dry wash, course SE. Asc. E. slope 250 ft.
 79.02 Point for the closing cor. of T. 26 N., Rs. 44 and 45 E.,
 hereinafter determined.

Land, rolling and broken mountainous. Soil, light, rocky gravelly clay. Undergrowth, sage, buckbrush and fair growth of grass.

West, on a true line, on the S. Bdy. of sec. 31.
 Asc. E. slope 80 ft. over rolling mountainous land.

1.70 Top of ridge, bears N. and S. Desc. W. slope 250 ft.
 18.40 Dry wash, course S. Asc. E. slope 390 ft.
 39.24 Intersect the E. Bdy. of T. 27 N., R. 44 E., at a point,
 North, 225 lks. dist., from the cor. of Ts. 26 and 27 N.,
 Rs. 44 and 45 E., hereinbefore described.

At the point of intersection, set an iron post, 3 ft.
 long, 3 ins. in diam., 27 ins. in the ground, for the
 closing cor. of Ts. 26 and 27 N., RS. 44 and 45 E.,
 with brass cap mkd.

T27N	T27N	
R44E	R45E	
S36	S31	C
	S1	C
	T26N	
	R44E	
	1925	

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, E. of the cor.