

Independent Resurvey of a portion of the S. Bdy. of
T. 27 N., R. 45 E.

Chains.

Note: markings and accessories of the cor. of Ts. 26 and 27 N., Rs. 44 and 45 E., hereinbefore described are changed as follows: An iron post, 3 ins. in diam., set 27 ins. in the ground, for the SE. cor. of T. 27 N., R. 44 E., only, with brass cap mkd.

T27N	
R44E	T26N ✓
S36	R44E
	S1
	1925

Raise a mound of stone, 3 ft. base, 2 ft. high, NW. of cor.

Land, rolling mountainous. Soil, rocky, gravelly clay. Undergrowth, sage, buckbrush and fair growth of grass.

Survey of the Fifth Standard Parallel N. through R. 45 E.

From the Standard cor. of T. 26 N., Rs. 45 and 46 E., which is an iron post, 3 ins. in diam., firmly set, and properly marked and witnessed, as described in the field notes of T. 26 N., R. 46 E.,

West, on a true line, on the S. Bdy. of sec. 36.

Asc. along NE. slope 220 ft. over rough mountainous land.

23.40 Dry wash, course NE. Asc. 300 ft. along SE. slope.

39.00 Same dry wash, course SE.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the Stand. $\frac{1}{4}$ cor. of sec. 36, with brass cap mkd.

SC
$\frac{1}{4}$ S36
1925

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.

Asc. E. slope 380 ft.

56.10 Top of spur, projects SE. Asc. along SE. slope 370 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the standard cor. of secs. 35 and 36, with brass cap mkd.

SC
T26N R45E
S35 S36