

Survey of the Fifth Standard Parallel N. through R. 45 E.

Chains.

Land, slightly rolling. Soil, sandy clay with strong alkaline content. Undergrowth, sage, shadscale and scant growth of grass.

West, on a true line, on the S. Bdy. of sec. 31.

Asc. gradual SE. slope.

31.00 Road, bears NE. and SW.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the standard $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{r} S\ C \\ \frac{1}{4} S31 \\ \hline 1925 \end{array}$$

At base of post, deposit a granite stone, 4 x 4 x 3 ins., marked with cross (x). No other accessories available.

48.20 Road, Beowawe to Austin, bears NE. and SW.

60.00 Dry wash, course SE.

71.80 Dry wash, course SE.

80.00 Set an iron post, 3 ft. long, 3 ins. in diam., 27 ins. in the ground, for the standard cor. of $\frac{1}{4}$ sec. 26 N., Rs. 44 and 45 E., with brass cap mkd.

$$\begin{array}{r} S\ C \\ T26N \\ R44E\ R45E \\ S36\ S31 \\ \hline 1925 \end{array}$$

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of the cor.

Land, slightly rolling. Soil, light, sandy and gravelly clay. Undergrowth, shadscale, sage and scant growth of grass.
