

Survey of the subdivisions of T. 26 N., R. 45 E.

Chains.

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.

Desc. NE. slope 340 ft.

50.40 Top of spur, projects N. Desc. N. slope 510 ft.

70.70 Dry wash, course NW. Asc. SW. slope 250 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 14 ins. in the ground, to solid rock, and 20 ins. in a mound of stone, for the cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

T26N	R45E
S26	S25
S35	S36
1925	

At base of post, deposit a granite stone, 8 x 8 x 6 ins., marked with cross (X).

Land, broken and mountainous. Soil, rocky and gravelly clay. Undergrowth, sage and fair growth of grass.

East, on a random line, bet. secs. 25 and 36.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.20 Fall 14 lks. S. of the cor. of secs. 25, 30, 31 and 36, which is an iron post, 2 ins. in diam., firmly set and properly marked and witnessed, as described in the field notes of T. 26 N., R. 46 E.

Thence

✓ S. 89° 54' W., on a true line, bet. secs. 25 and 36.

.40 Dry wash, course NE; Asc. NE. slope 230 ft. over broken mountainous land.

20.50 Top of spur, projects NE. Desc. NW. slope 20 ft.

26.60 Dry wash, course NE. Asc. E. slope 130 ft.

40.10 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$	S25
	S36
	1925

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.

Asc. 200 ft.

47.50 Shallow wash, course NE. Asc. E. slope 260 ft.