

Survey of the S. Bdy. of T. 25 N., R. 46 E.

Chains.

From the cor. of Ts. 24 and 25 N., Rs. 46 and 47 E.,
which is an iron post, 3 ins. in diam., firmly set and
properly marked and witnessed, as described in the field
notes of T. 25 N., R. 47 E.,

West, on a true line, on the S. Bdy. of sec. 36, on the
S. Bdy. of the township.

Desc. gradual W. slope 15 ft. over rolling land, through
scattering juniper.

1.70 Dry wash, course S. Asc. E. slope 60 ft.

8.50 Top of spur, projects S. Desc. W. slope 85 ft.

18.00 Dry wash, course S. Asc. E. slope 40 ft.

32.50 Top of spur, projects S. 20° W. Desc. W. slope 75 ft.

38.40 Dry wash, course S.

40.00 On gradual SE. slope, set an iron post, 3 ft. long, 1 in.
in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor.
for sec. 36, only, with brass cap mkd.

$\frac{1}{4}$ S36
1926

from which

A juniper, 6 ins. in diam., bears N. 12° W., 297 lks.
dist., marked $\frac{1}{4}$ S36 BT

A juniper, 6 ins. in diam., bears N. 75½° W., 211 lks.
dist., marked $\frac{1}{4}$ S36 BT

Asc. SE. slope 20 ft.

42.70 Top of low spur, projects S. Desc. gradual W. slope.

44.20 Dry wash, course S. Asc. gradual E. slope.

45.00 Top of low spur, projects S.

48.50 Top of low spur, projects S. 20° W. Desc. W. slope 80 ft.

70.60 Dry wash, course S.

72.90 Dry wash, course S. Asc. E. slope 30 ft.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins.
in the ground, for the cor. of secs. 35 and 36, only,
with brass cap mkd.

T25N | R46E
S35 | S36

1926

from which