

Dependent Resurvey of the W. Bdy. of T. 25 N., R. 46 E.

Chains.

- 4.51 The cor. of secs. 1 and 12, T. 25 N., R. 45 E., which is an iron post, 2 ins. in diam., firmly set and properly marked and witnessed as described in the field notes of T. 25 N., R. 45 E.
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 6, only, with brass cap mkd.

$\frac{1}{4}$
S6
1926

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of the cor.

Survey of the subdivisions of T. 25 N., R. 46 E.

From the cor. of secs. 35 and 36, on the S. Bdy. of the township, N. $0^{\circ} 01'$ W., bet. secs. 35 and 36.

Asc. along E. slope 140 ft. over rolling land, through scattering to medium growth of juniper.

- 32.70 Top of spur, projects SW. Desc. N. slope 55 ft.
- 39.70 Dry wash, drains W.
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S35 S36
1926

from which

A juniper, 4 ins. in diam., bears S. $75\frac{1}{4}^{\circ}$ E., 109 lks. distant, marked $\frac{1}{4}$ S36 BT

A juniper, 12 ins. in diam., bears N. $87\frac{1}{2}^{\circ}$ W., 33 lks. distant, marked $\frac{1}{4}$ S35 BT

Desc. NW. slope 25 ft.

- 42.50 Shallow wash, course W.
- 49.30 Dry wash, course W.
- 59.30 Dry wash, course W.
- 69.60 Dry wash, course SW. Asc. SE. slope 50 ft.
- 77.20 Top of low spur, projects SW.
- 80.00 On W. slope, set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 25, 26, 35, and 36, with brass cap mkd.