

Survey of the subdivisions of T. 25 N., R. 46 E.

Chains. in the ground, for the cor. of secs. 23, 24, 25 and 26,
with brass cap mkd.

T25N	R46E
S23	S24
S26	S25
1926	

from which

A juniper, 10 ins. in diam., bears N. $26\text{-}\frac{3}{4}^{\circ}$ E., 152 lks.
distant, marked T25N R46E S24 BT

A juniper, 6 ins. in diam., bears S. 68° E., 95 lks.
distant, marked T25N R46E S25 BT

A juniper, 12-ins. in diam., bears S. $30\text{-}\frac{3}{4}^{\circ}$ W., 121 lks.
distant, marked T25N R46E S26 BT

A juniper, 8 ins. in diam., bears N. $5\frac{1}{4}^{\circ}$ W., 98 lks.
distant, marked T25N R46E S23 BT

Land, rolling. Soil, light, sandy and gravelly clay.

Undergrowth, medium growth of sage; scant growth of
grass. Timber, medium growth of juniper.

N. $89^{\circ} 56'$ E., on a random line, bet. secs. 24 and 25.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.88 Fall 33 lks. N. of the cor. of secs. 19, 24, 25 and 30,
which is an iron post, 2 ins. in diam., firmly set and
properly marked and witnessed as described in the field
notes of T. 25 N., R. 47 E.

Thence

N. $89^{\circ} 50'$ W., on a true line, bet. secs. 24 and 25.

Asc. NE. slope 150 ft. over rolling mountainous land,
through scattering juniper timber.

9.30 Top of spur-ridge, projects S. from N. Desc. W. slope
210 ft.

31.60 Dry wash, drains SW. Asc. E. slope 60 ft.

37.30 Top of spur, projects S. for 10.00 chs. thence SW.
Desc. W. slope 30 ft.

39.94 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins.
in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$	S24
	S25
	1926