Survey of the subdivisions of T. 25 N., R. 46 E.

67.40 Dry wash, drains W. Asc. S. slope 50 ft. Top of spur, projects W. Desc. N. slope 30 ft. 73.30 Dry wash, drains W. Asc. S. slope 30 ft. 76.60 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. 80.00 in the ground, for the cor. of secs. 13, 14, 23 and 24, with brass cap mkd. T25N R46E from which A juniper, 10 ins. in diam., bears N. 47-3/4° E., 111 lks. distant, marked T25N R46E S13 BT A juniper, 5 ins. in diam., bears S. 29° E., 69 lks. distant, marked T25N R46E S24 BT A juniper, 5 ins. in diam., bears S. 5° W., 96 lks. distant, marked T25N R46E S23 BT nA juniper, 12 ins. in diam., bears N. 03/4° W., 58 lks. distant, marked T25N R46E S14 BT Land, rolling. Soil, light, sandy, gravelly and rocky clay. Undergrowth, medium growth of sage; scant growth of grass. Timber, medium growth juniper. S. 89° 50' E., on a random line, bet. secs. 13 and 24. 40.00 Set temp. \(\frac{1}{4}\) sec. cor. Fall 21 1ks. N. of the cor. of secs. 13, 18, 19 and 24, 79.86 which is an iron post, 2 ins. in diam., firmly set and properly marked and witnessed as described in the field notes of T. 25 N., R. 47 E. Thence N. 89° 41' W., on a true line, bet. secs. 13 and 24. Asc. SE. slope 170 ft. over rolling mountainous land, through scattering to medium growth of juniper. 8.60 Top of spur-ridge, projects S. from N. Desc. 50 ft. along NW. slope of spur 39.93 Set an iron post, 3 ft. long, 1 ins. in diam., 20 ins. in the ground, to solid rock and 16 ins. in a mound of stone, for the \(\frac{1}{4}\) sec. cor., with brass cap mkd.